

N 30, BUILT-IN OVEN, 60 X 60 CM, BLACK B1DCCOAK3B







2 x combination grid, 1 x universal pan

for professional pan, enamelled

Z11CR10X0 Baking and roasting grid (standard), Z11GU20X0 Glasspan, Z11TI15X0 Cliprails, Z11AB15A0 Baking tray, non-stick ceramic coated, Z11AU15A0 Universal pan, non-stick ceramic coated, Z12CM10A0 Moussaka pan, enamelled, Z12CN10A0 Professional pan, enamelled, Z12CP10A0 Pizza pan, enamelled, Z12CU10A0 Multipurpose pan, enamelled, Z1365WX0 Wireless food thermometer, Z1608BX0 Full ext rails, level independent, Z1650BE0 Half tray, Z1655CA0 Air Fry & Grill tray, Z1913X0 Baking Stone, Z12CB10A0 Baking tray, enamelled, Z12CL10A0 Lid

Optimal cooking results: CircoTherm $^{\tiny\textcircled{0}}$ hot-air system for simultaneous baking and roasting on up to 3 levels.

- $\sqrt{\mbox{ LED-Display}}$ simple, straightforward for clear reading
- $\sqrt{\rm CircoTherm^{\odot}}$ Smart hot-air solution that lets you bake on up to three levels at once.

Built-in / Free-standing:	1
Integrated Cleaning system:No)
Required niche size for installation (HxWxD): 585-595 x 560-568 x	
550 mm	
Dimensions:	1
Dimensions of the packed product (HxWxD): . 675 x 660 x 690 mm	1
Control Panel Material:	
Door Material:	
Net weight:]
Usable volume of cavity:	
Cooking method: Full width grill, Hotair gentle, Hot Air,	
Conventional heat, Hot air grilling	
Oven control: mechanical	
Length electrical supply cord:	
EAN code:	
Number of cavities (2010/30/EC):	
Energy efficiency rating:	
Energy consumption per cycle conventional (2010/30/EC): 0.94	
kWh/cycle	
Energy consumption per cycle forced air convection	
(2010/30/EC):	۵.
Energy efficiency index (2010/30/EC):	
Connection Rating:	
Fuse protection:	
Voltage:	
Frequency:	
Plug type:	Ī
(electrical connection by electrician)	
Included accessories:2 x combination grid, 1 x universal pan	1
The lades accessories	





N 30, BUILT-IN OVEN, 60 X 60 CM, BLACK B1DCCOAK3B

Features

- Oven with 5 main functions heating methods: CircoTherm®, Top/bottom heat, Circo-roasting, Full surface grill, CircoTherm® gentle
- Temperature range 50 °C 275 °C
- Cavity volume: 71 litre

Level independent telescopic rails

- 4 shelf positions
- Available as an accessory

Design

- Elongated designed dials, round
- Cavity inner surface: enamel anthracite

Cleaning

• Full glass inner door

Programmes/functions

- LED Display (Red)
- Electronic clock timer
- Heating up indicator
- Automatic start
- Bar handle
- Manual rapid heating up
- Interior halogen light
- Cooling fan
- Stainless-steel fan

Accessories

• 2 x combination grid, 1 x universal pan

Features

- Heat reflective glass
- Triple glazed door glazed CoolTouch door
- Control panel lock

Technical information

- 120 cm Cable length
- Nominal voltage: 220 240 V
- Total connected load electric: 2.99 KW

Performance/technical information

- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- • Niche dimension (hxwxd): 585 mm - 595 mm x 560 mm - 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



N 30, BUILT-IN OVEN, 60 X 60 CM, BLACK BIDCCOAK3B

