

### Series 6, Gas hob, 60 cm, Tempered glass, Black PPP6A6I40



#### **Optional accessories**


HEZ298105 Simmer plate
HEZ298114 Small pot support
HEZ32WA00 Wireless food thermometer

HEZ9SE040 4 pieces Set HEZ9SE060 6 pieces Set

# The gas hob with precise flame control and easy cleaning thanks to detachable metallic knobs and dishwasher suitable cast iron pan supports.

- Flame Select: Enjoy precise control of the flame.
- Tempered Glass: for strength and aesthetic.
- Easy cleaning: detachable dials and dishwasher-suitable pan supports make cleaning a breeze.
- Semi-continuous pan supports: smaller for easy cleaning, yet providing a seamless cooking surface.
- Standard and semi-flush built-in option: choose between flush or surface mounted installation.

### 



Frequency: ...... 50; 60 Hz





### Series 6, Gas hob, 60 cm, Tempered glass, Black PPP6A6I40

The gas hob with precise flame control and easy cleaning thanks to detachable metallic knobs and dishwasher suitable cast iron pan supports.

#### Design

- Tempered glass surface, Black
- frameless design: install the hob either flush or slightly raised on the worktop
- Cast iron pan supports with rubber feet

#### Usage convenience

- FlameSelect: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

#### **Burners and power**

- 4 gas burners:
- Left front: standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: high-speed burner up to 3 KW (depending on gas type)
- Right front: economy burner up to 1 KW (depending on gas type)

#### Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.
- Cast iron pan supports with rubber feet: little weight and compact form, yet high stability due to continuous surface.

#### Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

#### Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm):  $54 \times 590 \times 520$
- Required niche size for installation (HxWxD mm) :  $45 \times 560 \times (480 490)$
- Min. worktop thickness: 20 mm
- If installed flush, minimum worktop thickness is 30mm.
- Power cord: 1 m
- Connected load: 7.5 KW



## Series 6, Gas hob, 60 cm, Tempered glass, Black PPP6A6I40

