N 70, Gas hob, 75 cm, Enamel, Black T27CIQ8S0





Optional accessories

Z1365WX0Wireless food thermometerZ2471X0Wok ringZ9404SE04 pieces SetZ9406SE06 pieces Set

The gas hob with precise flame control, removable dials and pan supports that are suitable for dishwashers - for Comfort Clean.

- $\sqrt{}$ FlameSelect®: Gain precise control of your flame.
- $\checkmark\,$ Metallic Sword Dial: Precise and removable for easy cleaning. $\checkmark\,$ Cast Iron Pan Supports: For maximum stability and dishwasher
- cleaning.
- $\sqrt{1000}$ Wok Burner: Powerful cooking at up to 4 kW.
- $\checkmark\,$ Gas Safety Cut-Off: Safety first! No flame, no gas flow.

Features

Technical Data

Product name/family : gas hob w integrated controls Built-in / Free-standing : Built-in Energy input : Gas Total number of positions that can be used at the same time : 5 Required niche size for installation (HxWxD) : $45 \times 560-560 \times$ 480-490 mm Width of the appliance : 750 mm Dimensions : 51.5x750x520 mm Dimensions of the packed product (HxWxD) : $145 \times 793 \times 597$ mm Net weight : 14.2 kg Gross weight : 16.1 kg Residual heat indicator : Separate Location of control panel : Front Basic surface material : Enamel Color of surface : Black Length electrical supply cord : 100.0 cm EAN code : 4242004284628 Gas connection rating : 11500 W Fuse protection : 3 A Voltage : 220-240 V Frequency : 50; 60 Hz



N 70, Gas hob, 75 cm, Enamel, Black T27CIQ8S0



Features

Design

- enamel surface, black
- black cast iron pan supports with protective rubber feet
- full metal

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 4 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE) NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.5 x 750 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 490)
- Min. worktop thickness: 20 mm
- Power cord: 1 m
- Connected load: 11.5 KW

N 70, Gas hob, 75 cm, Enamel, Black T27CIQ8S0



