

# N 50, GAS HOB, 75 CM, STAINLESS STEEL T27GKQ8N0



Z2471X0 Wok ring
Z2480X0 Simmer plate
Z9404SE0 4 pieces Set
Z9406SE0 6 pieces Set
Z1365WX0 Wireless food thermometer

Z2402X0 Small pot support

The gas hob with pan supports that are suitable for dishwashers - for easy cleaning.

- $\sqrt{\,}$  Sword Dials: For easy, enjoyable control while cooking.
- $\sqrt{}$  Cast Iron Pan Supports: For maximum stability and dishwasher cleaning.
- $\sqrt{}$  Wok Burner: Powerful cooking at up to 3.3 kW.
- $\sqrt{}$  Gas Safety Cut-Off: Safety first! No flame, no gas flow.
- $\sqrt{\,}$  Biomethane Ready: Power your hob with renewable biomethane gas.

Product name/family:	gas hob w
integrated controls	
Built-in / Free-standing:	Built-in
Energy input:	Gas
Number of cooking zones:	
Type of control setting devices:	
Required niche size for installation (HxWxD):	
480-492 mm	13 X 300 302 X
Width of the appliance:	750 mm
Dimensions:	54.2x750x520 mm
Dimensions of the packed product (HxWxD):	
Net weight:	12.3 kg
Gross weight:	14.2 kg
Residual heat indicator:	without
Location of control panel:	Front
Basic surface material:	Stainless steel
Color of surface:	Stainless steel
Length electrical supply cord:	100.0 cm
EAN code:	
Gas connection rating:	
Fuse protection:	
Voltage:	
Frequency:	



## N 50, GAS HOB, 75 CM, STAINLESS STEEL T27GKQ8N0

#### Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet

#### Usage convenience

- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

### Burners and power

- 5 burner hob
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 3.3 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

### Cleaning

• Dishwasher suitable pan supports for easy cleaning.

#### Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

### Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm):  $54.2 \times 750 \times 520$
- Required niche size for installation (HxWxD mm) :  $45 \times 560 \times (480 - 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 10.8 KW



# N 50, GAS HOB, 75 CM, STAINLESS STEEL T27GKQ8N0

